Serial No.: 10/620,354

Docket No.: 107156-00193

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of the claims in

the above-captioned patent application.

Listing of Claims:

Claim 1. (Original) An organic electroluminescent display device comprising a

plurality of light-emitting elements formed of light-emitting films above a substrate each

containing organic electroluminescent materials and being sandwiched by a pair of

electrodes, wherein

each pixel of said display device is formed by two light-emitting elements

producing two different colors of predetermined chromaticity values, and

each of said colors has a gradation.

Claim 2. (Original) The organic electroluminescent display device according to

claim 1, wherein a mixture of said two different colors can produce a white color which is

designated by a white region in a CIE xy chromaticity diagram (JIS Z8110).

Claim 3. (Original) The organic electroluminescent display device according to

claim 1, wherein a mixture of said two different colors produces colors falling within a

circular area of a 0.1 radius with its center in a pure white coordinate (0.31, 0.316) in the

CIE xy chromaticity diagram.

TECH/370035.1

-2-

Serial No.: 10/620,354

Docket No.: 107156-00193

Claim 4. (Original) The organic electroluminescent display device according to

claim 1, wherein said two different colors are selected from red (R), green (G), blue (B),

cyan (C), magenta (M) and yellow (Y).

Claim 5. (Original) The organic electroluminescent display device according to

claim 1, wherein one of said two different colors is white and the other is one selected

from red (R), green (G), blue (B), cyan (C), magenta (M) and yellow (Y).

Claim 6. (Original) The organic electroluminescent display device according to

claim 1, wherein said chromaticity values of two different colors are controlled by

changing a concentration ratio of said organic electroluminescent materials or by

coupling with a foreign material.

Claim 7. (Original) The organic electroluminescent display device according to

claim 1, wherein said chromaticity values of two colors are controlled by changing

thickness of said light-emitting film.

Claim 8. (Original) The organic electroluminescent display device according to

claim 1, wherein said light-emitting elements are fabricated by a photo bleaching process

applied to said light-emitting film.

Claim 9. (Cancelled)

TECH/370035.1 -3-

Isamu OHSHITA et al.

Serial No.: 10/620,354

Docket No.: 107156-00193

Claim 10. (Currently Amended) The organic electroluminescent display device

according to claim [[9]] 1, wherein said color conversion filters are color filters each said

light-emitting element is formed corresponding to every color filter which converts a color

of light emitted from said light-emitting film, respectively.

Claim 11. (Currently Amended) The organic electroluminescent display device

according to claim [[9]] 1, wherein said color conversion filters are luminescent color

conversion filters each said light-emitting element is formed corresponding to every

luminescent color conversion filter which converts a color of light emitted from said light-

emitting film, respectively.

Claim 12. (Original) The organic electroluminescent display device according to

claim 1, wherein said light-emitting film is formed by a coating method or a printing

method.

Claim 13. (Original) The organic electroluminescent display device according to

claim 1, wherein said two different color light-emitting elements have different emissive

areas based on each lifetime of said light-emitting elements.

Claim 14. (Original) The organic electroluminescent display device according to

claim 1, wherein said light-emitting element is driven by an electric current of a different

level for each color.

TECH/370035.1

-4-

Isamu OHSHITA et al.

Serial No.: 10/620,354 Docket No.: 107156-00193

Claim 15. (Original) The organic electroluminescent display device according to claim 1, wherein said light-emitting element is driven by a voltage of a different level for each color.